



# BOBINAS PREFILTRO

Filtering media rolls  
Rouleaux filtrantes

[www.eu-filters.com](http://www.eu-filters.com)

<b>Manta filtrante</b> <i>Filtering media - Media filtrante:</i>	<b>Sintética</b> <i>Synthetic - Synthétique</i>
<b>Eficacia EN779</b> <i>Efficiency - Efficacité:</i>	G2, G3, G4
<b>Eficacia gravimétrica EN779</b> <i>Arrestance efficiency - Efficacité gravimétrique:</i>	65% (G2) - 85% (G3) - 90% (G4)
<b>Pérdida de carga inicial</b> <i>Initial pressure drop - Perte de charge initiale:</i>	31Pa (G2) - 33Pa (G3) - 35Pa (G4)
<b>Pérdida de carga final</b> <i>Final pressure drop - Perte de charge finale:</i>	250Pa
<b>Gramaje</b> <i>Weight - grammage:</i>	100gr/m2 (G2) - 150gr/m2 (G3) 200gr/m2 (G4)
<b>Espesor</b> <i>Thickness - épaisseur:</i>	10mm (G2) - 15mm (G3) - 20mm (G4)
<b>Capacidad de acumulación de polvo</b> - <i>Dust holding capacity</i> <i>Capacité d'accumulation de poussières:</i>	366gr/m2 (G3)
<b>Clasificación al fuego</b> <i>Flame resistance - Classement au feu:</i>	F1-K1 (DIN 53438) M1 (NF F-16-101-2:1998, NF P 92-507:2004)
<b>Temperatura máxima de trabajo</b> <i>Max. Working temp. - Température max. de travail:</i>	100°C

<b>Dimensiones</b> - <i>Sizes - Dimensions</i>	<b>Color</b> - <i>Colour - Couleur</i>	<b>Eficacia</b> - <i>Efficiency - Efficacité</i>
1x20m	<b>Blanca</b> - <i>White - blanc</i>	G2, G3, G4
1x20m	<b>Azul</b> - <i>Blue - Bleu</i>	G3
2x20m	<b>Blanca</b> - <i>White - blanc</i>	G2, G3, G4
1x50m	<b>Blanca</b> - <i>White - blanc</i>	G3, G4
2x50m	<b>Blanca</b> - <i>White - blanc</i>	G3, G4