



FILTROS BOLSAS G3/G4

Bag filters
Filtres à poches

www.eu-filters.com



vídeo

| | |
|---|---|
| Manta filtrante <i>Filtering media - Media filtrante:</i> | Sintética <i>Synthetic - Synthétique</i> |
| Eficacia EN779 <i>Efficiency - Efficacité:</i> | G3, G4 |
| Eficacia gravimétrica EN779 <i>Arrestance efficiency - Efficacité gravimétrique:</i> | 85% (G3) - 90% (G4) |
| Perfil <i>Frame - Cadre:</i> | Acero galvanizado <i>Galvanized Steel - Acier galvanisé</i> |
| Pérdida de carga final <i>Final pressure drop - Perte de charge finale:</i> | 250Pa |
| Capacidad de acumulación de polvo - Dust holding capacity <i>Capacité d'accumulation de poussières:</i> | 366gr/m2 |
| Clasificación al fuego <i>Flame resistance - Classement au feu:</i> | F1-K1 (DIN 53438) M1 (NF F-16-101-2:1998, NF P 92-507:2004) |
| Temperatura máxima de trabajo <i>Max. Working temp. - Température max. de travail:</i> | 100°C |

| Dimensiones <i>Sizes - Dimensions</i> | Nº de bolsas <i>Bags - Poches</i> | Caudal m3/h <i>Airflow - Debit</i> |
|--|--------------------------------------|---------------------------------------|
| 592x592x25/20x360mm | 8 | 3833 |
| 287x592x25/20x360mm | 4 | 1910 |
| 490x592x25/20x360mm | 6 | 2900 |
| 592x592x25/20x535mm | 8 | 5552 |
| 287x592x25/20x535mm | 4 | 2767 |
| 490x592x25/20x535mm | 6 | 4212 |
| 592x592x25/20x635mm | 8 | 6535 |
| 287x592x25/20x635mm | 4 | 3257 |
| 490x592x25/20x635mm | 6 | 4958 |

| Dimensiones <i>Sizes - Dimensions</i> | Nº de bolsas <i>Bags - Poches</i> | Caudal m3/h <i>Airflow - Debit</i> |
|--|--------------------------------------|---------------------------------------|
| 1068x532x25x250mm | 8 | 2750 |
| 990x460x25x450mm | 8 | 4135 |
| 1165x598x25x250mm | 8 | 3072 |
| 1196x587x25x250mm | 8 | 3043 |
| 1196x487x25x250mm | 8 | 2630 |
| 415x380x25x600mm | 1 | 924 |
| 450x590x25x600mm | 5 | 3962 |
| 935x622x25x430mm | 5 | 3432 |
| 920x498x25x350mm | 5 | 2390 |