



FILTROS BOLSAS M6

Bag filters

Filtres à poches

www.eu-filters.com

Manta filtrante

Filtering media - Media filtrante:

Sintética

Synthetic - Synthétique

Eficacia EN779

Efficiency - Efficacité:

M6

Eficacia opacimétrica EN779 2012

Opacimetric efficiency - Efficacité opacimétrique:

60%

Perfil

Frame - Cadre:

Acero galvanizado

Galvanized Steel - Acier galvanisé

Pérdida de carga final

Final pressure drop - Perte de charge finale:

450Pa

Clasificación al fuego

Flame resistance - Classement au feu:

F1-K1 (DIN 53438)

M1 (NF F-16-101-2:1998, NF P 92-507:2004)

Temperatura máxima de trabajo

Max. Working temp. - Température max. de travail:

100°C

Dimensiones Sizes - Dimensions	Nº de bolsas Bags - Poches	Caudal m3/h - Airflow - Debit			Sup M2	Pérdida de carga final Final pressure drop - Perte de charge finale		
		L	M	H		L	M	H
592x592x650mm	8	2520	3360	4200	7,02	52,50	80,00	112,50
592x592x650mm	10	3360	4200	5040	7,60	48,50	77,00	106,00
592x590x550mm	8	2520	3360	4200	5,94	47,50	75,00	105,00
592x592x550mm	10	3360	4200	5040	6,51	42,00	72,00	98,00
592x592x380mm	8	2520	3360	4200	4,10	55,00	85,00	115,00
490x592x650mm	6	2100	2814	3528	5,27	52,50	80,00	112,50
490x592x550mm	6	2100	2814	3528	4,46	47,50	75,00	105,00
490x592x380mm	6	2100	2814	3528	3,08	55,00	85,00	115,00
287x592x650mm	4	1260	2100	2520	3,51	52,50	80,00	112,50
287x592x650mm	5	1680	2520	2940	3,84	47,00	72,00	105,00
287x592x550mm	4	1260	1680	2100	2,97	47,50	75,00	105,00
287x592x380mm	4	1260	1680	2100	2,05	55,00	85,00	115,00