



## FILTROS CA-ECO

### Carbón activo manta impregnada

Activated charcoal  
impregnated media  
Charbon actif media  
imprégné

[www.eu-filters.com](http://www.eu-filters.com)

<b>Manta filtrante</b> <i>Filtering media - Media filtrante:</i>	<b>Sintética</b> <i>Synthetic - Synthétique</i>
<b>Eficacia EN779</b> <i>Efficiency - Efficacité:</i>	G4
<b>Capacidad de retención</b> <i>Dust holding capacity - Capacité d'accumulation de poussières:</i>	235gr/m2
<b>Perfil</b> <i>Frame - cadre:</i>	<b>Acero galvanizado</b> <i>Galvanized Steel - Acier galvanisé</i>
<b>Pérdida de carga inicial</b> <i>Initial pressure drop - Perte de charge initiale:</i>	48Pa
<b>Pérdida de carga final</b> <i>Final pressure drop - Perte de charge finale:</i>	200Pa
<b>Grosor manta filtrante</b> <i>Thickness media - Epaisseur media:</i>	22mm
<b>Clasificación al fuego</b> <i>Flame resistance - Classement au feu:</i>	F1-K1 (DIN 53438)
<b>Temperatura máxima de trabajo</b> <i>Max. Working temp. - Température max. de travail:</i>	100°C

Dimensiones <i>Sizes - Dimensions</i>	Unidades caja <i>Box - Carton</i>
490x490x25mm	12
390x490x25mm	12
495x495x25mm	12
497x497x25mm	12
490x250x25mm	24

Dimensiones <i>Sizes - Dimensions</i>	Unidades caja <i>Box - Carton</i>
592x592x25mm	40
490x490x48mm	6
390x490x48mm	6
592x592x48mm	20
287x592x48mm	40