



FILTROS HEPA flujo laminar

HEPA laminar flow
HEPA flux laminaire

www.eu-filters.com

Manta filtrante

Filtering media - Media filtrante:

Fibra de vidrio

Glass fiber - Fibre de verre

Eficacia EN1822

Efficiency - Efficacité:

H13, H14, U15

Eficacia gravimétrica

Arrestance efficiency - Efficacité gravimétrique:

≥99,95% (H13)
≥99,995% (H14)
≥99,9995% (U15)

Perfil

Frame - Cadre:

Aluminio

Aluminium

Junta

Gasket - Joint:

Poliuretano

Polyurethane

Pérdida de carga final

Final pressure drop - Perte de charge finale:

600Pa

Temperatura máxima de trabajo

Max. Working temp. - Température max. de travail:

80°C

Dimensiones Sizes - Dimensions	Superficie m2 Surface	Caudal m3/h Airflow - Debit
305x305x69mm	2,40	150
305x610x69mm	5,00	300
610x610x69mm	10,00	600
915x610x69mm	15,00	900
1220x610x69mm	20,00	1200

Dimensiones Sizes - Dimensions	Superficie m2 Surface	Caudal m3/h Airflow - Debit
305x305x78mm	2,80	150
305x610x78mm	5,50	300
610x610x78mm	10,50	600
915x610x78mm	15,50	900
1220x610x78mm	21,00	1200