



FILTROS DE MALLAS

Mesh filters

Filtres à mailles

www.eu-filters.com



video

Materia prima

Raw material

Matière première:

Aceros inoxidables AISI 430

y 304, y acero galvanizado

Stainless and galvanized steel

Acier inoxydable et acier galvanisé

Eficacia gravimétrica EN779

Arrestance efficiency - Efficacité gravimétrique:

65% (G2) 25mm grosor-Thickness-Épaisseur

85% (G3) 48mm grosor-Thickness-Épaisseur

Norma aplicable

Related standard - Norme applicable:

EN 779

Pérdida de carga inicial

Initial pressure drop - Perte de charge initiale:

40Pa

Pérdida de carga final

Final pressure drop - Perte de charge finale:

250 Pa

Velocidad frontal recomendada

Recommended face velocity - Vitesse frontale recommandée:

1,7m/s

Temperatura máxima de trabajo

Max. Working temp. - Température max. de travail:

350°C

Dimensiones Sizes - Dimensions	Unidades caja Box - Carton	Caudal m3/h Airflow - Debit
490x490x48mm	6	1480
390x490x48mm	6	1179
490x250x48mm	12	756
497x497x48mm	6	1512
495x495x48mm	6	1512
490x490x25mm	12	1247
390x490x25mm	12	993
490x250x25mm	24	636