



FILTROS SQ

Pleated filters
Filtres plissés

www.eu-filters.com



video

Manta filtrante

Filtering media - Media filtrante:

Sintética

Synthetic - Synthétique

Eficacia EN779

Efficiency - Efficacité:

G3, G4, M5

Eficacia gravimétrica EN779

Arrestance efficiency - Efficacité gravimétrique:

85% (G3) - 90% (G4)

Perfil

Frame - Cadre:

Acero galvanizado

Galvanized Steel - Acier galvanisé

Pérdida de carga final

Final pressure drop - Perte de charge finale:

250Pa

Capacidad de acumulación de polvo - Dust holding capacity

Capacité d'accumulation de poussières:

366gr/m2

Clasificación al fuego

Flame resistance - Classement au feu:

F1-K1 (DIN 53438)

M1 (NF F-16-101-2:1998, NF P 92-507:2004)

Temperatura máxima de trabajo

Max. Working temp. - Température max. de travail:

100°C

Dimensiones Sizes - Dimensions	Nº de pliegues Pleats - Plis	Caudal m3/h Airflow - Debit
592x592x48mm	12	3800
287x592x48mm	6	1900
490x592x48mm	10	3197
495x495x48mm	10	2673
490x490x48mm	10	2600
592x592x96mm	8	4000
287x592x96mm	4	2000
490x490x96mm	7	2730

Dimensiones Sizes - Dimensions	Nº de pliegues Pleats - Plis	Caudal m3/h Airflow - Debit
287x287x48mm	6	888
395x495x48mm	8	2108
622x395x48mm	13	2648
622x495x48mm	13	3319
800x500x48mm	16	4312
287x287x96mm	5	1142
490x592x96mm	7	4020
622x495x96mm	9	4267