



RECAMBIOS SQ

Pleated replacements
Recharges media plissé

www.eu-filters.com

Manta filtrante <i>Filtering media - Media filtrante:</i>	Sintética <i>Synthetic - Synthétique</i>
Eficacia EN779 <i>Efficiency - Efficacité:</i>	G3, G4
Eficacia gravimétrica EN779 <i>Arrestance efficiency - Efficacité gravimétrique:</i>	85% (G3) - 90% (G4)
Perfil <i>Frame - Cadre:</i>	Acero galvanizado <i>Galvanized Steel - Acier galvanisé</i>
Pérdida de carga final <i>Final pressure drop - Perte de charge finale:</i>	250Pa
Capacidad de acumulación de polvo - <i>Dust holding capacity</i> <i>Capacité d'accumulation de poussières:</i>	366gr/m2
Clasificación al fuego <i>Flame resistance - Classement au feu:</i>	F1-K1 (DIN 53438) M1 (NF F-16-101-2:1998, NF P 92-507:2004)
Temperatura máxima de trabajo <i>Max. Working temp. - Température max. de travail:</i>	100°C

Dimensiones <i>Sizes - Dimensions</i>	Nº de pliegues <i>Pleats - Plis</i>	Caudal m3/h <i>Airflow - Debit</i>
592x592x48mm	12	3800
287x592x48mm	6	1900
490x592x48mm	10	3197
495x495x48mm	10	2673
490x490x48mm	10	2600
287x287x48mm	6	888
395x495x48mm	8	2108
622x395x48mm	13	2648

Dimensiones <i>Sizes - Dimensions</i>	Nº de pliegues <i>Pleats - Plis</i>	Caudal m3/h <i>Airflow - Debit</i>
622x495x48mm	13	3319
800x500x48mm	16	4312