



FILTROS COMPACTOS

Compact filters
Filtres compactes

www.eu-filters.com

Manta filtrante

Filtering media - Media filtrante:

Fibra de vidrio

Glass fiber - Fibre de verre

Eficacia EN779

Efficiency - Efficacité:

M5, M6, F7, F8, F9

Eficacia gravimétrica

Arrestance efficiency - Efficacité gravimétrique:

40% (M5)
60% (M6)
80% (F7)
90% (F8)
95% (F9)

Perfil

Frame - Cadre:

Acero galvanizado

Galvanized Steel - Acier galvanisé

Pérdida de carga final

Final pressure drop - Perte de charge finale:

450Pa

Temperatura máxima de trabajo

Max. Working temp. - Température max. de travail:

100°C

Dimensiones Sizes - Dimensions	Superficie m2 Surface	Caudal m3/h Airflow - Debit
592x592x48mm	6,10	2000
287x592x48mm	3,05	1000
610x610x48mm	6,30	2100
305x610x48mm	3,15	1050

Dimensiones Sizes - Dimensions	Superficie m2 Surface	Caudal m3/h Airflow - Debit
592x592x96mm	11,25	3100
287x592x96mm	5,60	1550
610x610x96mm	11,60	3200
305x610x96mm	5,80	1600