



FILTROS PORTA MANTAS

Rechargeable panels
Panneaux rechargeables

www.eu-filters.com

Manta filtrante <i>Filtering media - Media filtrante:</i>	Sintética <i>Synthetic - Synthétique</i>
Eficacia EN779 <i>Efficiency - Efficacité:</i>	G3, G4
Eficacia gravimétrica EN779 <i>Arrestance efficiency - Efficacité gravimétrique:</i>	85% (G3) - 90% (G4)
Perfil <i>Frame - Cadre:</i>	Acero galvanizado <i>Galvanized Steel - Acier galvanisé</i>
Pérdida de carga final <i>Final pressure drop - Perte de charge finale:</i>	200Pa
Capacidad de acumulación de polvo - <i>Dust holding capacity</i> <i>Capacité d'accumulation de poussières:</i>	366gr/m ²
Clasificación al fuego <i>Flame resistance - Classement au feu:</i>	F1-K1 (DIN 53438) M1 (NF F-16-101-2:1998, NF P 92-507:2004)
Temperatura máxima de trabajo <i>Max. Working temp. - Température max. de travail:</i>	100°C

Dimensiones <i>Sizes - Dimensions</i>	Superficie m² <i>Surface</i>	Caudal m³/h <i>Airflow - Debit</i>
592x592x25mm	0,35	1500
287x592x25mm	0,17	750
490x592x25mm	0,29	1250
490x490x25mm	0,24	1000
592x592x20mm	0,35	1500
287x592x20mm	0,17	750
490x592x20mm	0,29	1250
490x490x20mm	0,24	1000